

WHITE OPAQUE

Design Blackout adhesive film



The White Opaque black out film provides comprehensive two-way privacy. Blocking almost all light penetration, this film provides an immediate and effective privacy solution, ideally suited for concealing stock, a storage area, etc.

Certifications



Warranty SOLAR SCREEN® 10 years See the 'New guarantees for

See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating M1



Storage From -5°C To +40°C 3 years



Reach Rohs Compliant Respected



Widths Available

Construction

- Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
- Dyed polyester without optical distortion, with anti IR metal particles deposit
- 3. Bonding adhesive
- 4. Dyed polyester without optical distortion
- 5. PS adhesive, glass polymerization within 15 days
- 6. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	1%
Reflection Of External Visible Light	88%
Reflection Of Internal Visible Light	88%
Total Solar Energy Rejected	86%
Total Solar Energy Rejected 2*	80%
Solar Ratio : Solar Energy Reflection	67%
Solar Energy Absorption	27%
Solar Energy Transmission	6%
Reduction In Solar Glare	100%
G-Value	0.13
U-Value	5
Shading Coefficient	0.1
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	150μ
Colour From The Outside	WHITE

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	1
Reflective Tinted Single Pane	✓
Clear Double Pane	- !
Tinted Double Pane	×
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	×
Stadip Ext. Clear Double Pane	×
Stadip Int. Clear Double Pane	×

✓ Yes

X Not Recommended

Caution

Cautio

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.